



# GLOBAL EAST ASIA TECHNOLOGY CO.,LIMITED

**Product name:** 2500-2700MHz Fiberglass Omni Antenna

**Product model:** GL-DY2600V8

**Applications:**

4G-LTE System  
Point to multipoint application

**Features:**

HighGain, Stable Performance  
HighQuality FiberglassRadome  
All Weather Operation



Electrical Specifications	
Frequency Range- MHz	2500-2700
VSWR	≤1.8
Gain- dBi	8
Horizontal beam width	360°
Verticalbeam width	15°
Polarization	Vertical
Input Impedance-Ω	50
Maximum input power- W	50
Lightning protection	DC Ground
Mechanical Specifications	
Input connector type	N-K
Connector place	Bottom
Dimensions- mm	Φ20×565
Antenna weight- kg	1.0
Radome material	Fiberglass
Radome color	gray
Operating temperature	-40°c~60°c
Rated Wind Velocity-m/s	60
Mounting hardware-mm	Φ 35~ Φ 60

Add: Room 826, Block B,BLDG 18, University Science Park(East), Zhengzhou City,P.R.Henan,China.  
Tel: 86-371-60911368 Email:info@global-antenna.com  
Web:<http://www.asialeren.com> <http://www.global-antenna.com>